


# Eagle 72HM G2

## 380-400 Watt

MONO PERC HALF CELL MODULE

Positive power tolerance of 0~+3%



### KEY FEATURES



#### Diamond Cell Technology

Uniquely designed high performance 5 busbar mono PERC half cell



#### High Voltage

UL and IEC 1500V certified; lowers BOS costs and yields better LCOE



#### Higher Module Power

Decrease in current loss yields higher module efficiency



#### Shade Tolerance

More shade tolerance due to twin arrays



#### PID FREE

Reinforced cell prevents potential induced degradation



#### Strength and Durability

Certified for high snow (5400Pa) and wind (2400 Pa) loads

- ISO9001:2008 Quality Standards
- ISO14001:2004 Environmental Standards
- OHSAS18001 Occupational Health & Safety Standards
- IEC61215, IEC61730 certified products
- UL1703 certified products

Nomenclature:


JKM400M-72HL-V

Code	Cell	Code	Cell	Code	Certification
null	Full	null	Normal	null	1000V
H	Half	L	Diamond	V	1500V





### LINEAR PERFORMANCE WARRANTY

10 Year Product Warranty • 25 Year Linear Power Warranty



## Engineering Drawings




## Packaging Configuration

( Two pallets = One stack )

26pcs/pallet, 52pcs/stack, 572pcs/40'HQ Container

## Electrical Performance & Temperature Dependence



## Mechanical Characteristics

Cell Type	Mono PERC Diamond Cell (158.75 x 158.75 mm)
No.of Half-cells	144 (6x24)
Dimensions	2008x1002x40mm (79.06x39.45x1.57 inch)
Weight	22.5 kg (49.6 lbs)
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67 Rated
Output Cables	12 AWG, Anode 1400mm(55.12 in), Cathode 1400mm(55.12 in) or Customized Length
Fire Type	Type 1

## SPECIFICATIONS

Module Type	JKM380M-72HL-V		JKM385M-72HL-V		JKM390M-72HL-V		JKM395M-72HL-V		JKM400M-72HL-V									
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT								
Maximum Power (Pmax)	380Wp	286Wp	385Wp	290Wp	390Wp	294Wp	395Wp	298Wp	400Wp	302Wp								
Maximum Power Voltage (Vmpp)	40.5V	38.6V	40.8V	38.8V	41.1V	39.1V	41.4V	39.3V	41.7V	39.6V								
Maximum Power Current (Impp)	9.39A	7.42A	9.44A	7.48A	9.49A	7.54A	9.55A	7.60A	9.60A	7.66A								
Open-circuit Voltage (Voc)	48.9V	47.5V	49.1V	47.7V	49.3V	48.0V	49.5V	48.2V	49.8V	48.5V								
Short-circuit Current (Isc)	9.75A	7.88A	9.92A	7.95A	10.12A	8.02A	10.23A	8.09A	10.36A	8.16A								
Module Efficiency STC (%)	18.89%		19.14%		19.38%		19.63%		19.88%									
Operating Temperature (°C)	-40°C~+85°C																	
Maximum System Voltage	1500VDC(UL)/1500VDC(IEC)																	
Maximum Series Fuse Rating	20A																	
Power Tolerance	0~+3%																	
Temperature Coefficients of Pmax	-0.36%/°C																	
Temperature Coefficients of Voc	-0.28%/°C																	
Temperature Coefficients of Isc	0.048%/°C																	
Nominal Operating Cell Temperature (NOCT)	45±2°C																	

STC: ☀ Irradiance 1000W/m<sup>2</sup>

Cell Temperature 25°C

Cloudy AM=1.5

NOCT: ☀ Irradiance 800W/m<sup>2</sup>

Ambient Temperature 20°C

Cloudy AM=1.5

Wind Speed 1m/s

\* Power measurement tolerance: ± 3%